







Configuration	Sidewall Height	Range of Capacities & Sizes
 Round Diameters range from 15 to 60 feet	22- to 44-inch	Minimum of 1,771 gallons (42 barrels)
 Square Sidewall sections are 112.5 inches long – minimums given are for a square 112.5 x 112.5 (larger units available)	22-inch 36-inch 44-inch	Minimum of 890 gallons (21 barrels) Minimum of 1,596 gallons (38 barrels) Minimum of 2,034 gallons (48 barrels)
 Rectangle Sidewall sections are 112.5 inches long – minimums given are for a unit one section wide by three sections long (larger units available)	22-inch 36-inch 44-inch	Minimum of 2,670 gallons (63 barrels) Minimum of 4,788 gallons (114 barrels) Minimum of 6,102 gallons (144 barrels)
 Oblong Diameters range from 15 to 60 feet and lengths from 24 to 135 feet	22- to 44-inch	Minimum of 3,188 gallons (76 barrels)
NOTE: All capacities are dependent on dimensions and height and are based on varying amounts of embedment and one-inch freeboard.		

Brock Industrial Systems • Milford, Indiana 46542-2000 U.S.A.

Phone +1 574-658-4191 • Internet: www.brockindustrial.com • E-Mail industrial@brockindustrial.com